

Designer: Alfredo Häberli
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge:
Weight: 430 g/mtl

Light resistance: 6-7
(ISO 1-8)
Abrasion: 100,000
Martindale
Colour: there may be slight
differences

The enviroment:
reduced environmental
impactFireproof test
BS 5852 Crib 5
BS 5852 part 1, ig. s. 0
DIN 4102 B1

EN 1021-1/2
FAR 25.853
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
ONORM B1/ Q1

SN 198 898 5.2
UNI 9175 11M
UNI 9177 Classe 1
US Cal. Bull. 117-2013



FD132



FD142



FD182



FD192



FD222




FD233



FD242



FD343



FD373



FD443



FD463



FD623



FD643



FD662



FD663



FD723



FD733



FD773



FD782



FD843



FD943



FD963

Composition: 100%
post-consumer recycled
polyester, including 50%
SEAQUAL yarn
Weight per square meter:

497 g/m² ±5% Heavy
duty / 10 year guarantee.
Independently
certified to ≥100,000
Martindale cycles

Fastness to Rubbing: Wet: 4,
Dry: 4 (ISO 105 - X12)
Flammability: EN 1021 - 1&2
Cigarette & Match
BS 7176 Low Hazard



OC01



OC02



OC03



OC04




OC05



OC06




OC07



OC08



OC10



OC11



OC12



OC13




OC14



OC15



OC16



OC09

E Volta Celeste

AURIM
TEXTILE ATTITUDE.

Composizione: 100% ImNativ PL
riciclato-biodegradabile Larghezza:
140 cm
Peso: 950 g/mtl (±4%)
Resistenza alla luce: 4 (ISO 105-B02)
Abrasione: 100.000 Martindale

Pilling: 4 (ISO 12945-2)
Solidità allo sfregamento: 4-5
(Asciutto) 4-5 (Bagnato) (ISO
105-X12)
Composition: 100% Recycled-
Biodegradable imNativ PL

Width: 140 cm
Weight: 950 g/mtl (±4%)
Light resistance: 4 (ISO 105-B02)
Abrasion: 100.000 Martindale
Pilling: 4 (ISO 12945-2)
Fastness to rubbing: 4-5 (Dry) 4-5

(Wet) ISO 105-X12
Test ignifugo - Fireproof test
TB-117:2013 California Test



No-shrink



VL100



VL105



VL309



VL404



VL604



VL408



VL409



VL410



VL411



VL600



VL601



VL603



VL606



VL804



VL805



VL811



VL900

Composition: 95% Wool, 3% Polyester, 2% Polyamide
Total width: 138 cm minimum
Weight per linear meter: 700 g/m2 ±5%
("Martindale") Abrasion

resistance. Heavy duty / 10 year guarantee. Independently certified to ≥50,000 Martindale cycles

Flammability
EN 1021 - 1&2 Cigarette & Match
BS 7176 Low Hazard
ONORM B 3825 & A 3800-1 (58kg/m3 CMHR Foam)

UNI 9175 Classe 1 IM
BS 5852 Ignition Source 5 when FR treated BS 7176 Medium Hazard when FR treated



YR01



YR02



YR03



YR04



YR12



YR14



YR15



YR16



YR17



YR18



YR20



YR25